
BS6883 INSTRUMENTATION

Fixed installations in all areas and on open deck in ships and offshore units.

CONDUCTOR	Tinned Copper
INSULATION	EPR
COLLECTIVE SCREEN	Collective Aluminium Mylar
ARMOUR	Galvanised Steel Wire Braid
OUTERSHEATH	LSZH
OUTERSHEATH COLOUR	Black
RATED VOLTAGE	250V
CORE IDENTIFICATION	Pairs: black and white (each pair numbered) Triples: black, white and red (each triple numbered) Quads: black, white, red and blue (each quad numbered)
MINIMUM BENDING RADIUS	Overall Bending Radius 8x
OPERATING TEMPERATURE	Minimum 90°C, minimum bending -25°C
STANDARDS	BS6883, IEC60332

SPECIFICATION DATA

BATT Part No	Cores	Nominal cross sectional Area mm2	Screen Type	Colour	Approx overall diameter	Weight
67740	2	0.75	CAM	Grey	12.9	240
67728	2	1.5	CAM	Grey	14	306
67736	2	1.5	CAM	Blue	14	306
67717	2	1.5	CAM	Black	14	306
67399	3	0.75	CAM	Grey	13.3	265
67324	3	1.5	CAM	Blue	14.5	309
67711	3	1.5	CAM	Black	14.5	309
67387	4	0.75	IND SCR	Grey	17.4	400
67195	4	0.75	IND SCR	Blue	17.4	400
67812	4	1.5	IAM/CAM	Blue	18	550
67485	4	1.5	IAM/CAM	Black	18	550
67206	6	0.75	IAM	Grey	19.1	525
67705	6	1.5	CAM	Black	20.8	539
67720	10	1.5	CAM	Black	23.8	810
67676	20	1.5	CAM	Black	29	1750

The information in this datasheet is for guidance only and subject to change without liability. Images provided are representations; actual cable dimensions may vary due to manufacturing tolerances.

www.battcables.com | 01322 441165

©2024 Batt Cables Limited

