

BW GLANDS

CMP BW brass glands for all types of steel wire armoured cables installed indoors.

Features:

- High quality durable materials
- Simple, effective two part arrangement
- Direct & remote installation
- Permanently crimped, low impedance earth termination
- Secure against self-loosening
- -60°C to +200°C
- Superior EMC performance

Kit Contents:


- Brass Gland
- Galvanised Locknut
- Earth Tag
- PVC Shroud

Additional Accessories available (upon request):

- Locknuts
- Earth Tags
- Nylon Washers
- Fibre Washers
- Serrated Washers

SPECIFICATION DATA

Batt Part No.	CMP Pack Reference	Gland Size	Thread	Thread Length (mm)	Cable Bedding Diameter "A"	Cable Diameter Range (mm) "B"	Armour Range (mm)		Weight (Kgs)
			"C"	"E"	Max	Max	Min	Max	
88344	20SBW2RA	20s	M20	10.0	11.7	15.8	0.8	1.25	0.05
88345	20BW2RA	20mm	M20	10.0	14.0	21.1	0.8	1.25	0.09
88346	25BW2RA	25mm	M25	10.0	20.0	27.2	1.25	1.6	0.11
88283	32BW2RA	32mm	M32	10.0	26.3	34.1	1.6	2.0	0.15
88284	40BW2RA	40mm	M40	15.0	32.2	42.4	1.6	2.0	0.32
88349	50SBW2RA	50s	M50	15.0	38.2	50.1	2.0	2.5	0.47
88350	50BW2RA	50mm	M50	15.0	44.1	55.7	2.0	2.5	0.48
88351	63SBW2RA	63s	M63	15.0	50.0	62.4	2.0	2.5	0.63
88352	63BW2RA	63mm	M63	15.0	56.0	68.2	2.0	2.5	0.89
88353	75SBW2RA	75s	M75	15.0	62.0	76.8	2.0	2.5	1.27
88354	75BW2RA	75mm	M75	15.0	68.0	82.9	2.5	3.0	1.40



The information in this datasheet is for guidance only and subject to change without liability. Images provided are representations; actual cable dimensions may vary due to manufacturing tolerances.

www.battcables.com | 01322 441165

©2024 Batt Cables Limited

