


## DEFENCE STANDARD 61-12 PART 4 (UNSCREENED) - LSZH



Multi-Core flexible cables designed for wiring between components within instruments and electronic equipment. commonly used in aircraft, computing, military vehicles and military equipment. This LSZH version, further increases safety in case of fire.

<b>CONDUCTOR</b>	Tinned Copper
<b>STRANDING</b>	Flexible
<b>INSULATION</b>	LSZH
<b>OUTERSHEATH</b>	LSZH
<b>OUTERSHEATH COLOUR</b>	Black
<b>MINIMUM BENDING RADIUS</b>	6 x overall diameter
<b>OPERATING TEMPERATURE</b>	70°C, Minimum bending: -15°C
<b>STANDARDS</b>	Defence standard 61-12 Part 5: Wires, cords & cables, electrical -metric units. Part 5 - cables, special purpose, electrical & cables, power, electrical (small multicore cables)

# SPECIFICATION DATA

BATT Part No	Cable identification code	No of cores	Diameter over laid up cores (mm)	Nominal overall diameter (mm)	Weight (kg/km)
35128	7-2-2A LSZH	2	2.4	3.4	13
35130	7-2-4A LSZH	4	2.9	3.9	20
35169	7-2-6A LSZH	6	3.6	4.6	30
35083	7-2-8A LSZH	8	4.1	5.1	38

The information in this datasheet is for guidance only and subject to change without liability. Images provided are representations; actual cable dimensions may vary due to manufacturing tolerances.

[www.battcables.com](http://www.battcables.com) | 01322 441165

©2024 Batt Cables Limited

