

NYLON CABLE TIES

Non-Releasable Cable Ties manufactured from Nylon 6.6 offering high resistance to bases, oils, greases and chloride solvents. Suitable for fixing cable bundles.

Specification:

Operating Temperature Range: -40°C to +85°C

Flame Resistance Testing: UL94 V2

Chemical Properties: High Resistance to: brake -fluids, lubricants, power steering -fluids, oil, grease, paints, lacquers, detergents, animal and vegetable fats, gasoline and alkalis up to 40%

Recommended Storage Temperature: +15°C to +30°C at 50% humidity

Material Options:

- Nylon 6.6
- LSF Zero Halogen DuPont Zytel 6.6

**Nylon LSF & Halogen Free Cable Tie to BSEN 61034-2 and tested to Smoke Density Method to ASTM D-2843*

SPECIFICATION DATA

Batt Part No	Length (mm)	Width (mm)	Max Bundle Diameter (mm)	Min. Tensile Strength (kg)	Colour	Material
66036	140	3.6	33	18	Black	Nylon
66037	160	4.8	39	22	Black	Nylon
66040	200	4.8	50	22	Black	Nylon
66059	200	4.8	50	22	Black	LSF
66038	300	4.8	76	22	Black	Nylon
66060	300	4.8	76	22	Black	LSF
66050	300	7.8	75	22	Black	Nylon
66074	365	4.8	102	22	Black	Nylon
66007	365	4.8	102	22	Black	LSF
66042	500	12.6	125	22	Black	Nylon

The information in this datasheet is for guidance only and subject to change without liability. Images provided are representations; actual cable dimensions may vary due to manufacturing tolerances.

www.battcables.com | 01322 441165

©2024 Batt Cables Limited

