
TELCLEAT LSOH

Single piece, single fixing low smoke zero halogen cleat.

Features:

- Manufactured from low smoke zero halogen (LSOH) polymer.
- Designed for use with LSOH and OHLS cables.
- Overlapping self-adjusting ranges.
- Sunlight (UV) and weather resistant.
- One piece, single fixing design.
- Can be double stacked on a single fixing.
- Operating temperature -40°C to +40°C.
- Tested in accordance with BS EN 50368.
- LUL approved product register ID 1259.

SPECIFICATION DATA

Batt Part No.	Cleat Reference	Cable Diameter (mm)		Dimensions (mm)				Weight	Roundhead Screw	Screw Bolt
				B		C	D			
		Min	Max	Min	Max	Max		(g)	ins x No	mm
90111	385LSF01	10.5	14.5	15	18	32	12	3.3	1 1/4" x 8	M4 x 30
90112	385LSF02	12.2	16.7	17	22	36	14	5.6	1 1/2" x 8	M4 x 35
90113	385LSF03	14.6	19.8	21	26	43	16	9.5	1 3/4" x 8	M4 x 40
90114	385LSF04	17.7	24.0	25	21	51	18	14.7	2" x 8	M4 x 45
90115	385LSF05	21.7	28.5	30	37	57	20	20.4	2 1/4" x 12	M4 x 50
90116	385LSF06	26.2	34.2	35	43	65	22	29.2	2 1/2" x 12	M4 x 60
90117	385LSF07	31.9	41.6	42	52	78	25	36.7	2 3/4" x 12	M4 x 80
90118	385LSF08	39.3	51.1	50	62	91	26	58.1	3 1/4" x 12	M6 x 80

Method of Fixing:

- The cleat is opened up and placed around the cable so that the end of the cleat containing the slot will be in contact with the mounting surface.
- When mounting directly on a channel section, an adaptor plate should be used (can be requested on demand).

Performance Data

Test Standard	EN 50368:2003
Type	6.1.2 Non-Metallic
Impact Resistance	6.2.4 Heavy -> 6.2.5 V. Heavy
Lateral Load	0.136 -> 0.781kN
Axial Load	0.119 -> 1.024 kN
Needle Flame	>120 secs

*Technical information can be subject to change without notice.

The information in this datasheet is for guidance only and subject to change without liability. Images provided are representations; actual cable dimensions may vary due to manufacturing tolerances.

www.battcables.com | 01322 441165

©2024 Batt Cables Limited

